



## SIGNAMAXX - SIG165

Ampronix introduces the SIGNAMAXX multi-modality video signal analyzer. Connect the Signamaxx to the video out from your modality and it will load the system's exact signal parameters - allowing Ampronix to custom program an LCD replacement for the existing CRT display.

With easy to use software and multiple video input options (D-Sub15 and single thru 5 BNC), the SIGNAMAXX is simple yet versatile. By covering signals from 525-1600 lines, color and/or grayscale, and Interlaced or Non- Interlaced/Progressive video, the SIGNAMAXX is the easiest way to ensure your transition from legacy CRT to new LCD technology is as smooth as possible. Signamaxx further simplifies things by transmitting your modality video signal parameters directly to Ampronix via the internet, saving you both time and money.

VIDEO INPUT INFORMATION	
Input Resolution	Analog: (H)15.7 – 90 kHz (V)50 – 120 Hz
Screen Size	15-Pin D-Sub 1-5 BNC (Accepts All Configurations)
Supports	Analog Interlaced and Non-interlaced Progressive Video
Power	VAC 100 – 240V 50 – 60Hz
Operating Temperature	55 °C
Weight	18 lbs
Connector	Power 3-Pin AC Plug
OPERATING ENVIRONMENT	
Connection Type	USB
Software	Provided With Unit

\*Patent Pending